



Specifications

Rating

15A 125 or 250VAC
 1/8HP 125VAC
 1/4HP 250VAC
 0.5A 125VDC
 0.25A 250VDC

Contact Resistance 15mΩ max.(initial)

Insulation Resistance 100MΩ min.(at 500V DC)

Dielectric Strength Between terminals of same polarity
 AC 1000V (50/60Hz for 1minute)

Electrically Life 100,000 operations min

Mechanically Life 1,000,000 operations min.

| | |
|---------|------------|
| OF max. | 100±10g |
| RF min. | 38 g |
| PT max. | 1.7 mm |
| OT min. | 7.0 mm |
| MD max. | 0.3 mm |
| FP max. | 44.85 mm |
| OP | 43.3±0.2mm |

加工處理方式

- △3
- △2
- △1
- △

審核: 白居瑪 繪圖: 陳國誠
 2020/10/05 2020/10/05
 茂仁電機業有限公司
 MOU JEN ELECTRIC CO.,LTD.

修改者 修改者 修改者

| | | |
|----------|--------------|-----------|
| TITLE | LEVER SWITCH | |
| MATERIAL | LEVER | SUS 304 |
| | HOUSING | PBT+15%GF |
| PART NO. | DM1-124 | |
| DWG NO. | MJ2-1730-BL | |
| SCALE | 1:1 | |